# JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094 PO Box 1519 - Gretna, LA 70054-1519



## PRODUCT BULLETIN

## **BIOCLEAN 4400**

## Remediation Cleaner, Dispersant, Degreaser

## General Description

BIOCLEAN 4400 is a general, all purpose concentrated cleaner that can tackle tough dirt, grime, and grease of all kinds. BIOCLEAN 4400 penetrates the soils quickly, holds them in suspension, and then rinses free, leaving a truly superior clean surface. It is effective in either hot or cold water applications and works with either hard or soft water. BIOCLEAN 4400 is phosphate-free and biodegradable, nonflammable, non-acid, non-caustic, and non-fuming. BIOCLEAN 4400's scope of applications is very wide because of the products strong cleaning abilities combined with it's mildness for everyday cleaning needs. BIOCLEAN 4400 is best used on any washable surface such as concrete, and asphalt floors, resilient tile floors, sealed woods, painted surfaces, and metal and plastic surfaces. BIOCLEAN 4400 has proven to be very effective in removal of surfaces contaminated with oil and grease containing PCB's. Whenever BIOCLEAN 4400 is used to clean PCB contaminated surfaces, the contractor should refer to EPA guidelines for handling and disposal of resulting wastes.

## Application/Dilution

Dilution rates vary depending on cleaning difficulty. Product can be sprayed or poured on surfaces to be cleaned. Allow ample time for the product to penetrate soils, scrub any stubborn areas, then rinse with hot or cold water. Remediation of aged or oxidized oils containing PCB's may be greatly improved by using hot water. Repeat as needed to lower contamination to acceptable levels.

### **Physical Properties**

Color Clear to Light Amber

Specific Gravity 1.01 - 1.03 pH 9.0 - 9.5 Freeze Point 32° F

#### **Dilutions**

For best results, use as provided or dilute **BIOCLEAN 4400** 1:5 in water for extremely soiled surfaces; 1:10 on moderately soiled surfaces; and 1:20 on oil spills. When used as a bilge cleaner, use 1:5 for extremely contaminated bilges, and up to 50:1 for normal oil control. Dilution rates for cleaning oxidized oils or tars must be determined on site by testing.

### **Availability**

**BIOCLEAN 4400** is available in UN approved 5 gallon pails, 55 gallon drums and bulk quantities.

### Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.