

JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094
PO Box 1519 - Gretna, LA 70054-1519



PRODUCT BULLETIN

ACID PRE-WASH 550SF

Acid Based Truck and Trailer Pre-Wash

General Description

Acid Pre-Wash 550SF is a clear blue liquid which contains inorganic acids and surface active agents that are specifically blended into a stable, highly active concentrate for the cleaning and brightening tractors and tractor trailers. **Acid Pre-Wash 550SF** *does not* contain Sulfuric Acid. Some of its uses include cleaning bright surfaces including aluminum, removal of light rust, corrosion protection through removal of salt deposits, conditioner of painted surfaces and conditioning aluminum surfaces.

Application

Acid Pre-Wash 550SF can be used as provided for heavy oxidation and scale or **Acid Pre-Wash 550SF** can be diluted in ratios of 1 : 1 to 1 : 15 in water depending on surfaces to be cleaned. **Acid Pre-Wash 550SF** can be applied with a brush or sprayer on wet surfaces. Apply from the bottom and work up allowing two to five minutes for penetration of the deposits. Rinse well with water while brushing in order to get a brighter surface. For fiberglass, use as provided, spray or brush onto surface, brush off deposits and rinse. Do not permit solution to dry on surface, rinse completely and preferably by covering area with a high pressure rinse. When used as directed, it is safe on aluminum, copper, Plexiglas, stainless steel, brass, iron, painted surfaces, steel, bronze, lead and rubber. Also very effective in removing brake dust and black carbon stains. It is not recommended for use on galvanized surfaces, zinc magnesium, chrome and tin.

Physical Properties

| | |
|------------------|-------------------|
| Color | Clear Blue Liquid |
| Odor | Typical Acid |
| Water Solubility | 100% |
| Density | 8.95 lbs./gallon |
| Freeze Point | 28BF |

Availability

Acid Pre-Wash 550SF is available in UN approved 5 gallon pails, 55 gallon drums and bulk quantities.

Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.