

JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094
PO Box 1519 - Gretna, LA 70054-1519



PRODUCT BULLETIN

SPEC FLOC 4200

Flocculent / Coagulant

General Description

SPEC FLOC 4200 is an acidic based flocculent / coagulant aid specifically formulated to de-water and dry waste materials containing reacted or un-reacted resins, acrylic or latex polymer slurries, and other types of industrial paint related wastes. It is effective in liquid/solids separation processes and sludge de-watering and waster water clarification.

Application

SPEC FLOC 4200 is designed to be injected neat into the application point through a variety of pumps or applied directly to the waste with agitation. The point of application should be selected to produce efficient mixing upstream of settling tanks or water handling systems. **SPEC FLOC 4200** compatibility testing is advised before using in mixing streams.

Physical Properties

Form @ 70BF	Dark Reddish Yellow Liquid
Odor	Slightly Acidic
Density @ 60BF	11.85 - 12.00 lbs./gal
pH	< 2.0
Freeze Point	< 32 ^B F
Flash Point, TCC	Non-Flammable

Availability

SPEC FLOC 4200 is shipped in UN approved bulk quantities or in 55 gallon non-returnable, plastic drums as a corrosive liquid.

Handling

Store in glass, plastic or epoxy-lined vessels in a protected area. Do not use aluminum or iron in feed or storage systems. Do not freeze. Observe warning label on containers. Normal precautions for industrial chemicals apply.