

JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094

PO Box 189 - Westwego, LA 70094-0189



PRODUCT BULLETIN

SPEC COOL 2000

Engine Cooling System Inhibitor

General Description

SPEC COOL 2000 is a liquid film-forming, water-based corrosion inhibitor designed for use in multi-metal systems operating at high or low temperatures. **SPEC COOL 2000** prevents deposits, scale, sludge and resulting losses in heat transfer or mechanical efficiency caused by high mineral waters.

Application

With water or commercial antifreeze solution, use minimum of 2.0 fl. Oz. of **SPEC COOL 2000** per gallon of cooling system capacity. If uninhibited, ethylene glycol solution is used, 4.0 fluid oz. per gallon of system capacity is recommended.

Physical Properties

Color	Red
Odor	Faint Organic
Solubility:	
Water	100%
Ethylene Glycol	15%
Boron (B ₂ O ₃)	4.2%
Density @ 60° F	10.1 lbs./gal
Flash Point	None
*Contains no chromates	*Does not deteriorate
*Low toxicity	*Prevents scale and sludge
*No affect on non-metals	*Compatible with antifreeze
*Inhibits multi-metal system	

Availability

SPEC COOL 2000 is available in UN approved 5 gallon pails and 55 gallon drums.

Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.