

JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094

PO Box 189 - Westwego, LA 70096



PRODUCT BULLETIN

SUN II

Water Soluble Corrosion / Rust Inhibitor

General Description

SUN II is a low foaming, water-based corrosion and rust protective coating which is extremely effective in inhibiting the attack of ferrous metals by aqueous solutions. **SUN II** provides effective protection of steel surfaces against high humidity conditions during extended indoor storage. When **SUN II** is applied to metal surfaces, it leaves behind a flexible water resistant barrier that will protect metal surfaces from moisture. **SUN II** does not contain any nitrites and/or nitrosating agents.

Application

SUN II can be applied by dipping the parts to be protected in a vat or spraying the parts to be protected with an air sprayer, pump type sprayers, or by pouring the product over the parts or wiping the surfaces with a sponge soaked in the product. Removal of the protective film is accomplished by cleaning with stripping agents.

Film thickness in microns when applied under average conditions is 2.5 (0.10 mils).

Physical Properties

Appearance	Opaque White
Odor	Mild Ammonia
Specific Gravity	1.01 – 1.04
Flash Point	None
pH @ 1% in water	8 - 9

Availability

SUN II is available in UN approved 5 gallon pails, 55 gallon drums and bulk qualities.

Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.