JMN SPECIALTIES, INC.

1100 Victory Drive - Westwego, LA 70094 PO Box 1519 - Gretna, LA 70054-1519



# **PRODUCT BULLETIN**

# **SPEC CUT 50** Metal Working Lubricant

#### General Description

**SPEC CUT 50** is a soluble oil concentrate specially designed to be a general purpose, multifunctional fluid for most ferrous and non ferrous materials and operations as diverse as cylindrical grinding, ID broaching and gear hobbing. **SPEC CUT 50** provides extended sump life while reducing carry off and leaves a fluid oily residue to prevent sticky ways and chunks. It is effective in some types of screw machines as a replacement for straight cutting oil and has EP additives to reduce chip welding and mechanical lubricity for good performance on soft gummy materials.

### **Application**

Always add **SPEC CUT 50** concentrate to the water with continuous stirring. NEVER THE REVERSE. Do not premix richer than 3 parts water to 1 part **SPEC CUT 50** concentrate (3:1). Premixing the initial charge and/or makeup solution outside of the machine sump is recommended. Do not add **SPEC CUT 50** concentrate directly to the working solution in the machine tool.

Light Duty Machining & Grinding:	5%
Moderate Duty Machining:	5%-7%
Heavy-Duty Machining:	7%-10%
Very Heavy-duty Machining:	10%-20%
Design Concentration Range:	5%-20%

Physical Properties	
Color	Greenish Liquid
Odor	Mild Solvent
Specific Gravity	.926
рН	9 - 10
Flash Point	> 300/F
Boiling Point	> 250/F
Freezing Point	< 32/F

## <u>Availability</u>

SPEC CUT 50 is available in UN approved 5 gallon pails, 55 gallon drums and bulk quantities.

#### Handling

Observe warning label on containers. Normal precautions for industrial chemicals apply.