

## **1 – PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME:	. QUICK SOLV
CHEMICAL NAME/	
CLASS/SYNONYMS:	Solvent Degreaser, Brake Cleaner, Non-chlorinated solvent cleaner
PRODUCT NUMBER:	. QUICK SOLV
UN/NA NUMBER:	. 1993
CHEMICAL FAMILY:	. Solvent
CAS NUMBER:	• Not applicable for mixtures.
FORMULA:	. Proprietary
COMPANY:	. JMN Specialties, Inc.
COMPANY:	<b>. JMN Specialties, Inc.</b> 1100 Victory Drive – Westwego, Louisiana USA 70094
COMPANY:	
COMPANY:	1100 Victory Drive – Westwego, Louisiana USA 70094
	1100 Victory Drive – Westwego, Louisiana USA 70094 Phone (504) 341-3749, Fax (504) 341-5868
	1100 Victory Drive – Westwego, Louisiana USA 70094 Phone (504) 341-3749, Fax (504) 341-5868 www.jmnspecialties.com
	<ul> <li>1100 Victory Drive – Westwego, Louisiana USA 70094</li> <li>Phone (504) 341-3749, Fax (504) 341-5868</li> <li>www.jmnspecialties.com</li> <li>CALL CHEMTEL: Toll Free US &amp; Canada: (800) 255-3924, Outside USA +01-813-248-0585.</li> </ul>

## 2 – HAZARDS IDENTIFICATION

### **GHS HAZARD CLASSIFICATION:**

## WARNING LABEL ITEMS INCLUDING PRECAUTIONARY STATEMENTS:



SIGNAL WORD:..... DANGER!

### GHS HAZARD AND PRECAUTIONARY STATEMENTS:

H225+H301+H311+H331+H370: Highly flammable liquid and vapor. Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled. Causes damage to organs.

P101+102+103: If medical advice is needed, have product container or label at hand. Keep out of the reach of children. Read label before use.

P202+270+280+281: Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.



P233+P210+P240+P241+P242+P243+P271+P280+P260+P264+P270: Keep container tightly closed. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product.

P501: Dispose of contents/container: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations, and product characteristics at time of disposal.

#### TOTAL VOC's:

5.92 pounds per gallon

### **3 - COMPOSITION / INFORMATION ON INGREDIENTS**

HAZARDOUS INGREDIENT	PERCENT	CAS NUMBER
Heptane	70 - 80	142-82-5
Denatured Ethanol	20 - 30	64-17-5

## 4 – FIRST-AID MEASURES

	Remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial resuscitation. Keep person warm and at rest. Treat symptomatically and supportively. Seek medical attention immediately. Qualified medical personnel should consider administering oxygen. Give large amounts of fresh water or milk immediately. Do not give anything by mouth if person is unconscious or otherwise unable to swallow. If vomiting occurs, keep head below hips to prevent aspiration. Treat symptomatically and supportively. Seek medical attention immediately.
EYES:	Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
	<ul> <li>Remove contaminated clothing and wash affected skin with soap and water. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.</li> <li>All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Material, if aspirated into the lungs, may cause chemical pneumonitis. Skin contact may aggravate an existing dermatitis. Treat appropriately.</li> </ul>



## **5 – FIRE-FIGHTING MEASURES**

GENERAL FIRE HAZARDS:	• Flammable liquid and vapor Flammable. In a fire or if heated, a pressure increase will occur and the contain may burst, with risk of subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Acidic gases formed. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. 545°F (285°C)
EXTINGUISHING MEDIA:	Determined by surrounding material. In case of fire, use water fog, dry
	chemical, $CO_2$ , or "alcohol" foam.
SPECIAL FIRE FIGHTING	
PROCEDURES:	Spilled product on ground may be slippery.
UNUSUAL FIRE AND	
EXPLOSION HAZARDS:	• Containers may explode from internal pressure if confined to fire. Cool with water spray. Vapor accumulation could flash or explode if in contact with an open flame.

## 6 – ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:	• Wear appropriate personal protective equipment before approaching spill site. For small spills, dilute with water to sewer if allowed by local and state regulations. If unable to wash product with water, absorb with inert material (sand or other approved material) and dispose of in accordance with applicable regulations.
WASTE DISPOSAL:	Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.
RCRA STATUS:	If discarded in its purchased form, this product is considered a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product should be classified as a hazardous waste. (40CFR261.20-24).



## 7 – HANDLING and STORAGE

STORAGE:	Keep in a tightly closed container, stored in a cool, dry, ventilated area below 44°C (110°F). Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Drum must not be washed out or used for other purposes.
HANDLING:	Avoid contact with eyes, skin and clothing. Do not inhale vapors and fumes. Wash thoroughly after handling. Use only with adequate ventilation. Do not take internally. For industrial use only.

### 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

## **OCCUPATIONAL EXPOSURE LIMITS**

HAZARDOUS INGREDIENT	PEL	TLV-TWA
Heptane	400 ppm	400 ppm
Denatured Ethanol	250 ppm	250 ppm



**EXPOSURE CONTROLS:** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

**RESPIRATORY PROTECTION:** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information. Self-Contained Breathing Apparatus may be required for use in confined or enclosed spaces. **PROTECTIVE CLOTHING:** 

**PROTECTIVE CLOTHING: Eye/face protection:** Wear chemical goggles; face shield (if splashing is possible). **Skin protection:** Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron or chemical suit and chemical resistant boots are recommended.



**ADDITIONAL MEASURES:** 

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

## 9 – PHYSICAL / CHEMICAL PROPERITES

<b>BOILING POINT:</b>	209.3°F (98.5°C)
FREEZING POINT:	-131.1°F (-90.6°C)
FLASHPOINT:	25°F (-3.89°C)
UPPER FLAME LIMIT (%):	. 6.7%
LOWER FLAME LIMIT (%):	. 1.2%
VAPOR PRESSURE:	4.6 kPa (34.50 mm Hg) [room temperature]
VAPOR DENSITY (AIR=1):	• 3.46 (Air = 1)
SPECIFIC GRAVITY:	. 0.70 - 0.73
pH:	.NA
SOLUBILITY IN WATER:	Not Soluble
VOLATILITY	
<b>INCLUDING WATER:</b>	5.92 pounds per gallon
MOLECULAR WEIGHT:	No data available (G/MOLE)
EVAPORATION RATE:	. ND
PHYSICAL STATE:	. Liquid
COLOR:	. Clear
ODOR:	. Characteristic

### **10 – STABILITY and REACTIVITY**

STABILITY:	Stable
HAZARDOUS DECOMP.:	Will not occur
INCOMPATIBILITY:	Halocarbons, combustible materials, metals, oxidizing materials,
	halogens, metal carbide, bases, acids, amines.
HAZARDOUS REACTIONS:	Not expected to be Explosive, Self-Reactive, Self-Heating, or an
	Organic Peroxide under US GHS Definition(s).

## 11 – TOXICOLOGICAL INFORMATION

**Cancer:** Research shows that the Solvents used in the mixture are unlikely to cause cancer. **Reproductive Effects:** There are no indications that the Solvents used in the mixture causes damage to reproductive organs. Solvents may affect the development of unborn babies. **Organ Systems:** Damage to the brain, liver, bone marrow and kidneys can occur with repeated or excessive inhalation of any solvent vapors.

THRESHOLD LIMIT VALUE:.	. 200 ppm
OSHA PEL:	<b>.</b> 200 ppm
LISTED CARCINOGEN:	. CARCINOGENIC EFFECTS: Not available. MUTAGENIC
	EFFECTS: Not available. TERATOGENIC EFFECTS: Not available.
	DEVELOPMENTAL TOXICITY: Not available. The substance may
	be toxic to lungs, peripheral nervous system, upper respiratory tract,
	skin, central nervous system (CNS). Repeated or prolonged exposure to
	the substance can produce target organs damage.
MEDICAL CONDITION	
AGGRAVATED:	Existing dermatitis.



## INFORMATION ON ACUTE TOXICOLOGICAL EFFECTS

### ORAL

## DERMAL

### INHALATION

**Product:** Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. May cause narcotic effects in high concentration. Causes upper respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness. Aspiration of material into the lungs may be fatal.

#### **REPEATED DOSE TOXICITY**

#### SKIN CORROSION / IRRITATION

#### SERIOUS EYE DAMAGE / IRRITATION

#### **RESPIRATORY OR SKIN SENSITIZATION**

#### MUTAGENCITY

#### 

#### CARCINOGENICITY

**Product:.....** Based on available data, the classification criteria are not met. **REPODUCTIVE TOXICITY** 

## SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE

**Product: INHALATION:** High concentrations of vapor may cause irritation of the respiratory tract, experienced as nasal discomfort and discharge, with chest pain and coughing. Headache, nausea, vomiting, dizziness, and drowsiness may occur. **EYES:** Causes severe irritation experienced as discomfort or pain, excess blinking and tear production, with marked excess redness and swelling of the conjunctiva. **SKIN:** Brief contact may cause slight irritation with itching and local redness. Prolonged contact may cause more severe irritation, with discomfort or pain. **SWALLOWING:** Poison, toxic. May cause headache, dizziness, incorrdination, nausea, vomiting, diarrhea, and general weakness. **MAY BE FATAL IF SWALLOWED.** 



### SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE

been determined. Safe handling of this material on a long-term basis should emphasize the avoidance of all effects from repetitive acute exposure. This product may aggravate existing eye, skin, and respiratory conditions.

#### **ASPIRATION HAZARD**

Product: ...... Droplets of the product aspirated into the lungs through ingestion or vomiting may cause chemical pneumonia.

#### **OTHER ADVERSE EFFECTS**

For Heptane: LC50 Inhalation Gas. Rat 48000 ppm 4 hours, LC50 Inhalation Vapor Rat **Product:** 50242 ppm 1 hours, LC50 Inhalation Vapor Rat 103 g/m<sup>3</sup> 4 hours.

### **12 – ECOLOGICAL INFORMATION**

#### ACUTE TOXICITY

#### FISH

LL50: 1.284 mg/l, Exposure time: 96 hour, Species: Oncorhynchus mykiss (rainbow **Product:** trout). LC50: 375 mg/l, Exposure time: 96 hour, Species: Tilapia mosambica (Fish).

#### **AOUATIC INVERTEBRATES**

**Product:** EC50: 1.5 mg/l, Exposure time: 48 hour, Species: Daphnia magna (Water flea). Static test Toxic to aquatic organisms. LC50: 0.1 mg/l, Exposure time: 96 hour, Species: Mysidopsis bahia (mysid shrimp), semi-static test. Very toxic to aquatic organisms.

#### CHRONIC TOXICITY

#### FISH

**Product:**.....NOEC/NOEL > 100 mg/l. (based on similar products / components) **AQUATIC INVERTEBRATES** 

TOXICITY TO AQUATIC PLANTS

**Product:** EL50: 4.338 mg/l, Exposure time: 72 hour, Species: Pseudokirchneriella subcapitata.

#### PERSISTENCE AND DEGRADABILITY

#### **BIODEGRADATION**

**BIOLOGICAL OXYGEN DEMAND** 

#### **Product:** BOD: 1.92 g O<sup>2</sup>/g

CHEMICAL OXYGEN DEMAND **Product:** 

COD: 0.06 g O<sup>2</sup>/g

**BOD / COD RATIO** 

Product: ..... No data available

#### **BIOACCUMULATIVE POTENTIAL**

unlikely.

#### MOBILITY IN SOIL

to most soil types.

#### **RESULTS OF PBT AND mPvB ASSESSMENT**

fulfilling vPvB (very persistent, very bioaccumulative) criteria.



### **OTHER ADVERSE EFFECTS**

**Product:** ...... No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

### **13 – DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL:	Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in
RCRA STATUS:	accordance with federal, state and local requirements. If discarded in its purchased form, this product is considered a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product should be classified as a hazardous waste. (40CFR261.20-24).

## 14 – TRANSPORTATION INFORMATION

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.





## **15 - REGULATIONS**

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System. This SDS complies with 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD). **IMPORTANT:** Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

### EPA SRA Title III Chemical Listings:

 TSCA STATUS:
 This product is listed on the TSCA inventory. If this product is a blend, all ingredients in the product are listed on the TSCA Inventory List. Any impurities present in this product are exempt from listing.

 SECTION 302:
 None

 SECTION 304:
 None

 SECTION 312:
 None

 SARA SECTION 313:
 None

 SARA SECTION 313:
 None

 SPRESSURE:
 Yes

 FIRE:
 Yes

 PRESSURE:
 No

 CLEAN WATER ACT:
 No data available

### IMDG – International Marine Dangerous Goods Code

UN1993, Flammable liquid, n.o.s., Contains (Heptane, Ethanol), 3, F+, PGII. EmS F-E, S-E. Marine Pollutant: No Static Accumulator: Yes.

IATA

UN1993, Flammable liquid, n.o.s., Contains (Heptane, Ethanol), 3, F+, PGII.

DEA Chemical Trafficking Act: .. No



## **16 – OTHER INFORMATION**

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	ON H

\*HMIS®HAZARD INDEX: 0=Minimal Hazard, 1=Slight Hazard, 2=Moderate Hazard, 3=Serious Hazard, 4=Severe Hazard. HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this SDS and product label must be considered.

ND = No Data, NA = Not Applicable/Not Available,  $\leq$  = Less than or equal to,  $\geq$  = Greater than or equal to

**REVISION STATEMENT:** Changes have been made throughout this Safety Data Sheet (SDS). Please read the entire document. Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and The Globally Harmonized System of Classification and Labeling of Chemicals (GHS) by the Company Health and Risk Assessment Unit.

### **DISCLAIMER:**

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, the Company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving this Safety Data Sheet (SDS) will make their own determination as to its suitability for their intended purposes prior to use. Since the product is within the exclusive control of the user, it is the user's obligation to determine the conditions of safe use of this product. Such conditions should comply with all Federal and State Regulations concerning the Product. It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. NO REPRESENTATIONS OR WARRANTIES, EITHER **EXPRESS** OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH **INFORMATION REFERS.** 

\*\*\*This is the last page of this SDS\*\*\*