

1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:.....SDG 5250 CLEANER

CHEMICAL NAME/

UN/NA NUMBER: 1268

CHEMICAL FAMILY: Compounds, Cleaning Liquid

CAS NUMBER: Mixture

FORMULA: A complex stream of predominately C9 to C12 hydrocarbons; exact

composition will vary.

COMPANY:.....JMN Specialties, Inc.

1100 Victory Drive - Westwego, Louisiana USA 70094

Phone (504) 341-3749, Fax (504) 341-5868

www.jmnspecialties.com

EMERGENCY PHONE: CALL CHEMTEL: Toll Free US & Canada: (800) 255-3924, Outside

USA +01-813-248-0585.

DATE PREPARED: February 28, 2019

2 - HAZARDS IDENTIFICATION

GHS HAZARD CLASSIFICATION:

Physical Hazards

Health Hazards

Skin Corrosion/Irritation: Catagory 2 - Causes skin irritation **Serious Eye Damage/Irritation:** Catagory 2A - Causes eye irritation

Aspiration Hazard:...... Catagory 1 - May be fatal if swallowed and enters airways

WARNING LABEL ITEMS INCLUDING PRECAUTIONARY STATEMENTS:

Pictograms:







SIGNAL WORD:......DANGER!

GHS HAZARD AND PRECAUTIONARY STATEMENTS:

H303 H313 H333: May be harmful if swallowed, in contact with skin or if inhaled H305: May be harmful if swallowed and enters airways

P101+102+103: If medical advice is needed, have product container or label at hand. Keep out of the reach of children. Read label before use.

P202+270+280+281: Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.



P501: Dispose of contents/container: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

TOTAL VOC's: 6.47 pounds per gallon

3 - COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	PERCENT	CAS NUMBER
Petroleum Solvent Naphtha, Heavy Aromatic	50 - 60	64742-95-6
Xylene	30 - 40	106-42-3

4 - FIRST-AID MEASURES

BREATHING (INHALATION): Remove from exposure area to fresh air immediately. If breathing has

stopped, perform artificial resuscitation. Keep person warm and at rest. Treat symptomatically and supportively. Seek medical attention immediately. Qualified medical personnel should consider

administering oxygen.

SWALLOWING (INGESTION): Give large amounts of fresh water or milk immediately. Do not give

anything by mouth if person is unconscious or otherwise unable to swallow. If vomiting occurs, keep head below hips to prevent aspiration. Treat symptomatically and supportively. Seek medical

attention immediately.

occurs, obtain medical attention.

SKIN (DERMAL):...... Remove contaminated clothing and wash affected skin with soap and

water. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent

immediately to a hospital. Do not wait for symptoms to develop.

NOTE TO PHYSICIAN: All treatments should be based on observed signs and symptoms of

distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Material, if aspirated into the lungs, may cause chemical pneumonitis. Skin contact may aggravate an existing dermatitis. Treat

appropriately.

5 – FIRE-FIGHTING MEASURES

GENERAL FIRE HAZARDS: Flammable liquid and vapor

AUTOIGNITION TEMP: 842°F (450°C)

EXTINGUISHING MEDIA: Determined by surrounding material. In case of fire, use water fog, dry

chemical, CO₂, or "alcohol" foam.



SPECIAL FIRE FIGHTING PROCEDURES: UNUSUAL FIRE AND

Spilled product on ground may be slippery.

EXPLOSION HAZARDS:...... Containers may explode from internal pressure if confined to fire. Cool with water spray. Vapor accumulation could flash or explode if in contact with an open flame.

6 – ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:..... Wear appropriate personal protective equipment before approaching spill site. For small spills, dilute with water to sewer if allowed by local and state regulations. If unable to wash product with water, absorb with inert material (sand or other approved material) and dispose of in accordance with applicable regulations.

WASTE DISPOSAL: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

RCRA STATUS:....

If discarded in its purchased form, this product is considered a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product should be classified as a hazardous waste. (40CFR261.20-24).

7 - HANDLING and STORAGE

STORAGE:

Keep in a tightly closed container, stored in a cool, dry, ventilated area below 44°C (110°F). Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Drum must not be washed out or used for other purposes.

fumes. Wash thoroughly after handling. Use only with adequate ventilation. Do not take internally. For industrial use only.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS INGREDIENT PEL **TLV-TWA** Petroleum Solvent Naphtha, Heavy Aromatic 10 ppm 10 ppm Xylene 100 ppm 100 ppm









EXPOSURE CONTROLS: Good general ventilation (typically 10 air changes per hour) should be

used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most

recent edition, for details.

RESPIRATORY PROTECTION: If engineering controls do not maintain airborne concentrations below

recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable) air-purifying filter, cartridge

government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information. Self-Contained Breathing Apparatus may be

required for use in confined or enclosed spaces.

PROTECTIVE CLOTHING: Eye/face protection: Wear chemical goggles; face shield (if splashing

is possible). **Skin protection:** Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron or chemical suit and chemical resistant boots

are recommended.

ADDITIONAL MEASURES: Handle in accordance with good industrial hygiene and safety practice.

Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be

available close to work areas.

9 - PHYSICAL / CHEMICAL PROPERITES

BOILING POINT: 352°F (178°C) **FREEZING POINT:** - 4°F (-20°C) **FLASHPOINT:** 150°F (65.5°C)

pH: NA
SOLUBILITY IN WATER:..... Negligible

VOLATILITY

INCLUDING WATER: 7.89 pounds per gallon
MOLECULAR WEIGHT: No data available (G/MOLE)

EVAPORATION RATE: 0.05
PHYSICAL STATE: Liquid
COLOR: Clear

ODOR:..... Aromatic solvent



10 - STABILITY and REACTIVITY

STABILITY: Stable

HAZARDOUS DECOMP .:.... Will not occur

INCOMPATIBILITY: Oxidizers or Oxidizing Materials.

HAZARDOUS REACTIONS: Not expected to be Explosive, Self-Reactive, Self-Heating, or an

Organic Peroxide under US GHS Definition(s).

11 - TOXICOLOGICAL INFORMATION

Cancer: Research shows that the Solvents used in the mixture are unlikely to cause cancer. **Reproductive Effects:** There are no indications that the Solvents used in the mixture causes damage to reproductive organs. Solvents may affect the development of unborn babies. **Organ Systems:** Damage to the brain, liver, bone marrow and kidneys can occur with repeated or excessive inhalation of any solvent vapors.

THRESHOLD LIMIT VALUE:.. 10 ppm

OSHA PEL:.... 10 ppm

LISTED CARCINOGEN:.............. No data available for the mutagenic, teratogenic, or reproductive effects

of the property. No data to designate product to cause specific target

organ toxicity through repeated exposure.

MEDICAL CONDITION

AGGRAVATED: Existing dermatitis.

INFORMATION ON ACUTE TOXICOLOGICAL EFFECTS

ORAL

Product:...... Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death. **DERMAL**

INHALATION

REPEATED DOSE TOXICITY

SKIN CORROSION / IRRITATION

Product: Repeated and prolonged exposure to concentrated material may cause dermatitis.

SERIOUS EYE DAMAGE / IRRITATION

Product: Practically non-irritating. Slightly irritating but does not injure eye tissue.

RESPIRATORY OR SKIN SENSITIZATION



MUTAGENCITY

of the property.

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

Product: GENERAL: Solvent vapors may be irritating to skin and eyes. **INHALATION:** High concentrations of vapor may cause irritation of the respiratory tract, experienced as nasal discomfort and discharge, possibly with chest pain and coughing. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. **EYES:** May cause mild to severe rritation experienced as discomfort or pain, excess blinking and tear production, possibly with marked redness and swelling of the conjunctiva. **SKIN:** Brief contact may cause slight irritation with itching and local redness. Prolonged contact may cause more severe irritation, with discomfort or pain. **SWALLOWING:** May cause headache, dizziness, nausea, vomiting, diarrhea, coma, and death.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE

ASPIRATION HAZARD

Product:...... Droplets of the product aspirated into the lungs through ingestion or vomiting may cause chemical pneumonia.

OTHER ADVERSE EFFECTS

Product: LD $_{50}$ (oral) 7050, 8400mg/kg (rat), above 5000mg/kg (rat), LD50 (skin) >2000 & >3160mg/kg (rabbit) - no mortality recorded in these tests. LC $_{50}$ (inhalation) 5100 & 11,400mg/m 3 (rat), above 590mg/m 3 (rat). Chronic Toxicity NOAEL (oral) 300mg/kg/day (rats - various toxic symptoms - 90 days). LOAEL (skin) 119mg/kg (applied twice weekly - 50 weeks) (mouse, lung symptoms). NOAEC (inhalation) 2430mg/m 3 (rats - reproduction).

12 - ECOLOGICAL INFORMATION

ACUTE TOXICITY

FISH

Product: LC₅₀ (Fish, 96hr) >50mg/liter (Pimephelas promelas)

AOUATIC INVERTEBRATES

Product: EC_{50} (Crustacea, 48hr) > 140mg/liter (Diatomus forbesi)



CHRONIC TOXICITY

FISH

Product: This material has exhibited slight toxicity to terrestrial organisms.

AQUATIC INVERTEBRATES

Product: This material has exhibited slight toxicity to terrestrial organisms.

TOXICITY TO AQUATIC PLANTS

EC₅₀ (Algae) 2.5mg/liter (Skeletonema costatum), 4.2mg/liter (Selenastrum **Product:**

capricornutum)

PERSISTENCE AND DEGRADABILITY

BIODEGRADATION

Product: Readily Biodegradable.

BIOLOGICAL OXYGEN DEMAND

Product:.....

CHEMICAL OXYGEN DEMAND

Product: No data available

BOD / COD RATIO

Product: No data available

BIOACCUMULATIVE POTENTIAL

Product: Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

MOBILITY IN SOIL

Product: Negligible

RESULTS OF PBT AND mPvB ASSESSMENT

fulfilling vPvB (very persistent, very bioaccumulative) criteria.

OTHER ADVERSE EFFECTS

photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

RCRA STATUS:...... If discarded in its purchased form, this product is considered a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product should be classified as a hazardous waste. (40CFR261.20-24).



14 - TRANSPORTATION INFORMATION

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.



UN/NA NUMBER: 1268

PROPER SHIPPING NAME: Petroleum Distillates, n.o.s., Contains (Heavy Petroleum Naphtha)

HAZARD CLASS:......3
PACKAGING GROUP:......III

LETTER:.... F (Highly flammable)

ENVIRONMENTAL HAZARD: Because of modern treatment methods or method of use of this product,

only an insignificant amount of the ingredients reaches the environment. That amount is at such levels as to typically not cause any adverse

effects.

REPORTABLE QUANTITY:.... None

15 - REGULATIONS

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System. This SDS complies with 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD). **IMPORTANT:** Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

EPA SRA Title III Chemical Listings:

TSCA STATUS:	This product is listed on the TSCA inventory. If this product is a blend,
	all ingredients in the product are listed on the TSCA Inventory List.
	Any impurities present in this product are exempt from listing.
SECTION 302:	None
SECTION 304:	None
SECTION 312:	Yes
SARA SECTION 313:	None
ACUTE:	Yes
CHRONIC:	Yes
FIRE:	Yes
PRESSURE:	No
REACTIVE:	No
CLEAN WATER ACT:	None

IMDG – International Marine Dangerous Goods Code

UN1268, Petroleum Distillates, N.O.S. Contains (Heavy Petroleum Naphtha), 3, PG III. EMS-No: F-E S-E. Marine pollutant: No.

IATA

UN1268, Petroleum Distillates, N.O.S. Contains (Heavy Petroleum Naphtha), 3, PG III.

DEA Chemical Trafficking Act:.. No



16 - OTHER INFORMATION

HMIS*		
HEALTH	1	
FLAMMABILITY	2	
REACTIVITY	0	
PERSONAL PROTECTION	ON C	

*HMIS®HAZARD INDEX: 0=Minimal Hazard, 1=Slight Hazard, 2=Moderate Hazard, 3=Serious Hazard, 4=Severe Hazard. HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this SDS and product label must be considered.

ND = No Data, NA = Not Applicable/Not Available, \leq = Less than or equal to, \geq = Greater than or equal to

REVISION STATEMENT: Changes have been made throughout this Safety Data Sheet (SDS). Please read the entire document. Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and The Globally Harmonized System of Classification and Labeling of Chemicals (GHS) by the Company Health and Risk Assessment Unit.

DISCLAIMER:

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, the Company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving this Safety Data Sheet (SDS) will make their own determination as to its suitability for their intended purposes prior to use. Since the product is within the exclusive control of the user, it is the user's obligation to determine the conditions of safe use of this product. Such conditions should comply with all Federal and State Regulations concerning the Product. It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. REPRESENTATIONS OR WARRANTIES, **EITHER EXPRESS** OR IMPLIED, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

This is the last page of this SDS