

1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:	. RP-900
CHEMICAL NAME/	
CLASS/SYNONYMS:	. MIL-PRF-32033
PRODUCT NUMBER:	. RP-900
UN/NA NUMBER:	. None
CHEMICAL FAMILY:	. Corrosion Inhibitor
CAS NUMBER:	Not applicable for mixtures.
FORMULA:	. Proprietary
COMPANY:	. JMN Specialties, Inc.
COMPANY:	. JMN Specialties, Inc. 1100 Victory Drive – Westwego, Louisiana USA 70094
COMPANY:	• · · · ·
COMPANY:	1100 Victory Drive – Westwego, Louisiana USA 70094
	1100 Victory Drive – Westwego, Louisiana USA 70094 Phone (504) 341-3749, Fax (504) 341-5868
	1100 Victory Drive – Westwego, Louisiana USA 70094 Phone (504) 341-3749, Fax (504) 341-5868 www.jmnspecialties.com
	 1100 Victory Drive – Westwego, Louisiana USA 70094 Phone (504) 341-3749, Fax (504) 341-5868 www.jmnspecialties.com CALL CHEMTEL: Toll Free US & Canada: (800) 255-3924, Outside USA +01-813-248-0585.

2 – HAZARDS IDENTIFICATION

GHS HAZARD CLASSIFICATION:

WARNING LABEL ITEMS INCLUDING PRECAUTIONARY STATEMENTS:

Pictograms:



SIGNAL WORD:..... WARNING!

GHS HAZARD AND PRECAUTIONARY STATEMENTS:

H303 H313 H333: May be harmful if swallowed, in contact with skin or if inhaled H305: May be harmful if swallowed and enters airways

P101+102+103: If medical advice is needed, have product container or label at hand. Keep out of the reach of children. Read label before use.

P202+270+280+281: Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.



P501: Dispose of contents/container: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

TOTAL VOC's: 2 pounds per gallon

3 – COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	PERCENT	CAS NUMBER
Distillates (petroleum), hydrotreated light naphthenic	40 - 90	64742-53-6
Paraffin oils (petroleum), catalytic dewaxed light	10 - 40	64742-71-8

4 – FIRST-AID MEASURES

	Remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial resuscitation. Keep person warm and at rest. Treat symptomatically and supportively. Seek medical attention immediately. Qualified medical personnel should consider administering oxygen. Give large amounts of fresh water or milk immediately. Do not give
	anything by mouth if person is unconscious or otherwise unable to swallow. If vomiting occurs, keep head below hips to prevent aspiration. Treat symptomatically and supportively. Seek medical attention immediately.
EYES:	Flush eye with copious quantities of water. If persistent irritation
	 occurs, obtain medical attention. Remove contaminated clothing and wash affected skin with soap and water. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Material, if aspirated into the lungs, may cause chemical pneumonitis. Skin contact may aggravate an existing dermatitis. Treat appropriately.



5 – FIRE-FIGHTING MEASURES

GENERAL FIRE HAZARDS: No special fire hazards are known to be associated with this product.		
Dense smoke may be generated while burning.		
AUTOIGNITION TEMP:	. 650 - 700°F (343 - 371°C), Estimated	
EXTINGUISHING MEDIA:	Determined by surrounding material. In case of fire, use water fog, dry chemical, CO_2 , or "alcohol" foam. Firefighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.	
SPECIAL FIRE FIGHTING PROCEDURES: UNUSUAL FIRE AND	Spilled product on ground may be slippery.	
	• Containers may explode from internal pressure if confined to fire. Cool with water spray. Vapor accumulation could flash or explode if in contact with an open flame.	

6 – ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:	 Wear appropriate personal protective equipment before approaching spill site. For small spills, dilute with water to sewer if allowed by local and state regulations. If unable to wash product with water, absorb with inert material (sand or other approved material) and dispose of in accordance with applicable regulations. Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with
RCRA STATUS:	applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. If discarded in its purchased form, this product is considered a RCRA
	hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product should be classified as a hazardous waste. (40CFR261.20-24).

7 – HANDLING and STORAGE

STORAGE:	Keep in a tightly closed container, stored in a cool, dry, ventilated area below 44°C (110°F). Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe
	all warnings and precautions listed for the product. Drum must not be
	washed out or used for other purposes.
HANDLING:	• Avoid contact with eyes, skin and clothing. Do not inhale vapors and
	fumes. Wash thoroughly after handling. Use only with adequate
	ventilation. Do not take internally. For industrial use only.



8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS INGREDIENT	PEL	TLV-TWA
Distillates (petroleum), hydrotreated light naphthenic	5 mg/m ³ (Oil Mist)	5 mg/m ³ (Oil Mist)
Paraffin oils (petroleum), catalytic dewaxed light	5 mg/m ³	5 mg/m ³



EXPOSURE CONTROLS:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Please refer to the ACGIH document, <i>Industrial Ventilation, A Manual of Recommended Practices</i> , most
	recent edition, for details.
RESPIRATORY PROTECTION	N: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information. Self-Contained Breathing Apparatus may be required for use in confined or enclosed spaces.
PROTECTIVE CLOTHING:	Eye/face protection: Wear chemical goggles; face shield (if splashing is possible). Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron or chemical suit and chemical resistant boots are recommended.
ADDITIONAL MEASURES:	Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

9 – PHYSICAL / CHEMICAL PROPERITES



LOWER FLAME LIMIT (%):	. NA
VAPOR PRESSURE:	. < 0.01 mm/HG @ 212°F (100°C)
VAPOR DENSITY (AIR=1):	. > 1
SPECIFIC GRAVITY:	. 0.89 - 0.91
pH:	NA
SOLUBILITY IN WATER:	Negligible
VOLATILITY	
INCLUDING WATER:	7.50 pounds per gallon
MOLECULAR WEIGHT:	No data available (G/MOLE)
EVAPORATION RATE:	Slower than Ethyl Ether
PHYSICAL STATE:	. Liquid
COLOR:	Amber to Brown
ODOR:	Bland Hydrocarbon
	-

10 – STABILITY and REACTIVITY

 STABILITY:
 Stable

 HAZARDOUS DECOMP.:
 Will not occur

 INCOMPATIBILITY:
 Oxidizers or Oxidizing Materials.

 HAZARDOUS REACTIONS:
 Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).

11 – TOXICOLOGICAL INFORMATION

This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydrotreating. None of the oils requires a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B). These oils have not been classified by the American Conference of Governmental Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).

 THRESHOLD LIMIT VALUE:.. 5 mg/m³ (Oil Mist)

 OSHA PEL:
 5 mg/m³ (Oil Mist)

 LISTED CARCINOGEN:
 No data available for the mutagenic, teratogenic, or reproductive effects of the property. No data to designate product to cause specific target organ toxicity through repeated exposure.

 MEDICAL CONDITION
 AGGRAVATED:

 Existing dermatitis.

INFORMATION ON ACUTE TOXICOLOGICAL EFFECTS

ORAL



INHALATION

REPEATED DOSE TOXICITY

Product:..... No data available for the mutagenic, teratogenic, or reproductive effects of the property. No data to designate product to cause specific target organ toxicity through repeated exposure.

SKIN CORROSION / IRRITATION

SERIOUS EYE DAMAGE / IRRITATION

RESPIRATORY OR SKIN SENSITIZATION

MUTAGENCITY

IN VITRO

 Product:
 No Data Available

 IN VIVO
 Product:

 Product:
 No Data Available

 Specified Substance(s)
 Information as provided by manufacturer

 Petroleum Oils
 No Data Available

CARCINOGENICITY

Product:......Based on available data, the classification criteria are not met. **REPODUCTIVE TOXICITY**

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

Product: GENERAL: Solvent vapors may be irritating to skin and eyes. **INHALATION:** High concentrations of vapor may cause irritation of the respiratory tract, experienced as nasal discomfort and discharge, possibly with chest pain and coughing. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. **EYES:** May cause mild to severe rritation experienced as discomfort or pain, excess blinking and tear production, possibly with marked redness and swelling of the conjunctiva. **SKIN:** Brief contact may cause slight irritation with itching and local redness. Prolonged contact may cause more severe irritation, with discomfort or pain. **SWALLOWING:** May cause headache, dizziness, nausea, vomiting, diarrhea, coma, and death.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE

ASPIRATION HAZARD

OTHER ADVERSE EFFECTS

Product: Negligible ecotoxicity



12 – ECOLOGICAL INFORMATION

ACUTE TOXICITY

FISH

Product:......Not determined. Keep product out of sewers and waterways. **AQUATIC INVERTEBRATES**

Product:.....Not determined. Keep product out of sewers and waterways.

CHRONIC TOXICITY

FISH

PERSISTENCE AND DEGRADABILITY

BIODEGRADATION

Product: CHEMICAL OXYGEN DEMAND

Product: No data available

BOD / COD RATIO

Product: No data available

BIOACCUMULATIVE POTENTIAL

Product:..... Expected to partition to sediment and wastewater solids.

MOBILITY IN SOIL

Product: Negligible

RESULTS OF PBT AND mPvB ASSESSMENT

OTHER ADVERSE EFFECTS

Product: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.



RCRA STATUS:..... If discarded in its purchased form, this product is considered a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product should be classified as a hazardous waste. (40CFR261.20-24).

14 – TRANSPORTATION INFORMATION

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.

UN/NA NUMBER:	. None
PROPER SHIPPING NAME:	Non-Regulated
HAZARD CLASS:	None
PACKAGING GROUP :	. None
LETTER:	. None
ENVIRONMENTAL HAZARD:	Because of modern treatment methods or method of use of this product, only an insignificant amount of the ingredients reaches the environment.
	That amount is at such levels as to typically not cause any adverse
	effects.
REPORTABLE QUANTITY:	. None

15 - REGULATIONS

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System. This SDS complies with 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD). **IMPORTANT:** Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

EPA SRA Title III Chemical Listings:

SECTION 302:	None
SECTION 304:	None
SECTION 312:	None
SARA SECTION 313:	
ACUTE:	Yes
CHRONIC:	
FIRE:	
PRESSURE:	No
REACTIVE:	
CLEAN WATER ACT:	

IMDG – International Marine Dangerous Goods Code Class Non Regulated - Possible Shipping Description(s): Non Regulated IATA

Class Non Regulated - Possible Shipping Description(s): Non Regulated



DEA Chemical Trafficking Act:.. No

16 – OTHER INFORMATION

HMIS*		
HEALTH		0
FLAMMABILITY		1
REACTIVITY		0
PERSONAL PROTECTION		В

***HMIS®HAZARD INDEX: 0=Minimal Hazard, 1=Slight Hazard, 2=Moderate Hazard, 3=Serious Hazard, 4=Severe Hazard.** HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this SDS and product label must be considered.

ND = No Data, NA = Not Applicable/Not Available, \leq = Less than or equal to, \geq = Greater than or equal to

REVISION STATEMENT: Changes have been made throughout this Safety Data Sheet (SDS). Please read the entire document. Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and The Globally Harmonized System of Classification and Labeling of Chemicals (GHS) by the Company Health and Risk Assessment Unit.

DISCLAIMER:

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, the Company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving this Safety Data Sheet (SDS) will make their own determination as to its suitability for their intended purposes prior to use. Since the product is within the exclusive control of the user, it is the user's obligation to determine the conditions of safe use of this product. Such conditions should comply with all Federal and State Regulations concerning the Product. It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH **INFORMATION REFERS.**

This is the last page of this SDS