

### 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:..... SPEC SOL 1306

CHEMICAL NAME/

CLASS/SYNONYMS: ...... Paraffin Dispersant PRODUCT NUMBER: ..... SPEC SOL 1306

UN/NA NUMBER: ..... 1268

CHEMICAL FAMILY: ..... Petroleum Solvent

**CAS NUMBER:** ...... Not applicable for mixtures.

composition will vary.

COMPANY:.....JMN Specialties, Inc.

1100 Victory Drive - Westwego, Louisiana USA 70094

Phone (504) 341-3749, Fax (504) 341-5868

www.jmnspecialties.com

EMERGENCY PHONE: ...... CALL CHEMTEL: Toll Free US & Canada: (800) 255-3924, Outside

USA +01-813-248-0585.

**DATE PREPARED:** ...... May 29, 2019

#### 2 - HAZARDS IDENTIFICATION

#### GHS HAZARD CLASSIFICATION:

Physical Hazards

**Health Hazards** 

**Skin Corrosion/Irritation:** ...... Catagory 2 - Causes skin irritation **Serious Eye Damage/Irritation:** Catagory 2A - Causes eye irritation

### WARNING LABEL ITEMS INCLUDING PRECAUTIONARY STATEMENTS:

**Pictograms:** 







SIGNAL WORD:..... DANGER!

#### GHS HAZARD AND PRECAUTIONARY STATEMENTS:

H303 H313 H333: May be harmful if swallowed, in contact with skin or if inhaled

H305: May be harmful if swallowed and enters airways

P101+102+103: If medical advice is needed, have product container or label at hand. Keep out of the reach of children. Read label before use.

P202+270+280+281: Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.



P501: Dispose of contents/container: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

TOTAL VOC's: ...... 7.29 pounds per gallon

### 3 - COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	PERCENT	CAS NUMBER
Petroleum Solvent Naphtha, Heavy Aromatic	45 - 65	64742-94-5
Toluene	45 - 65	108-88-3
Poly(oxy-1,2-ethanediyl), alpha-(4-nonylphenyl)- omega-hydroxy-, branched	0.5 - 1.5	127087-87-0

### 4 - FIRST-AID MEASURES

BREATHING (INHALATION):	Remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial resuscitation. Keep person warm and at rest.
	Treat symptomatically and supportively. Seek medical attention immediately. Qualified medical personnel should consider administering oxygen.
SWALLOWING (INGESTION):	Give large amounts of fresh water or milk immediately. Do not give anything by mouth if person is unconscious or otherwise unable to swallow. If vomiting occurs, keep head below hips to prevent aspiration. Treat symptomatically and supportively. Seek medical
EYES:	attention immediately. Flush eye with copious quantities of water. If persistent irritation
SKIN (DERMAL):	occurs, obtain medical attention.  Remove contaminated clothing and wash affected skin with soap and water. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can
NOTE TO PHYSICIAN:	occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility
	that overexposure to materials other than this product may have occurred. Material, if aspirated into the lungs, may cause chemical pneumonitis. Skin contact may aggravate an existing dermatitis. Treat appropriately.



### 5 - FIRE-FIGHTING MEASURES

GENERAL FIRE HAZARDS: .... Flammable liquid and vapor

**AUTOIGNITION TEMP:.....** 842°F (450°C)

**EXTINGUISHING MEDIA:** Determined by surrounding material. In case of fire, use water fog, dry

chemical, CO<sub>2</sub>, or "alcohol" foam. Firefighting should be attempted only by those who are adequately trained and equipped with proper

protective equipment.

**SPECIAL FIRE FIGHTING** 

**PROCEDURES:** 

Spilled product on ground may be slippery.

UNUSUAL FIRE AND

**EXPLOSION HAZARDS:.....** Containers may explode from internal pressure if confined to fire. Cool

with water spray. Vapor accumulation could flash or explode if in

contact with an open flame.

### 6 - ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES: ...... Wear appropriate personal protective equipment before approaching

spill site. For small spills, dilute with water to sewer if allowed by local and state regulations. If unable to wash product with water, absorb with inert material (sand or other approved material) and dispose of in

accordance with applicable regulations.

WASTE DISPOSAL: ...... Treatment, storage, transportation and disposal must be in accordance

with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in

accordance with federal, state and local requirements.

RCRA STATUS:...... If discarded in its purchased form, this product is considered a RCRA

hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product should

be classified as a hazardous waste. (40CFR261.20-24).

#### 7 - HANDLING and STORAGE

**STORAGE:** Keep in a tightly closed container, stored in a cool, dry, ventilated area

below 44°C (110°F). Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Drum must not be

washed out or used for other purposes.

**HANDLING:** Avoid contact with eyes, skin and clothing. Do not inhale vapors and

fumes. Wash thoroughly after handling. Use only with adequate

ventilation. Do not take internally. For industrial use only.



### 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS INGREDIENT

Petroleum Solvent Naphtha, Heavy Aromatic

Toluene

Poly(oxy-1,2-ethanediyl), alpha-(4-nonylphenyl)omega-hydroxy-, branched

**PEL** 

**TLV-TWA** 

100 ppm 100 ppm 50 ppm 50 ppm

None Established

None Established









**EXPOSURE CONTROLS:** 

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

RESPIRATORY PROTECTION: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information. Self-Contained Breathing Apparatus may be

PROTECTIVE CLOTHING:

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible). Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron or chemical suit and chemical resistant boots are recommended.

required for use in confined or enclosed spaces.

**ADDITIONAL MEASURES:** 

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.



### 9 - PHYSICAL / CHEMICAL PROPERITES

**BOILING POINT:....** IBP 231.8°F (111°C)

**FREEZING POINT: .....** - 4°F (-20°C)

**FLASHPOINT:** 44.6°F (7°C) TCC Typical

**UPPER FLAME LIMIT** (%): .... 7.0% **LOWER FLAME LIMIT** (%): ... 0.6% **VAPOR PRESSURE**:...... ND **VAPOR DENSITY** (AIR=1):...... > 1

CRECIEIC CDANIEN 200

**SPECIFIC GRAVITY: .....** 0.88 - 0.89 **pH: .....** NA

**SOLUBILITY IN WATER:.....** Negligible

**VOLATILITY** 

EVAPORATION RATE: ...... 0.05 PHYSICAL STATE: ..... Liquid

COLOR: ...... Clear to Light Amber ODOR: ..... Aromatic solvent

### 10 - STABILITY and REACTIVITY

STABILITY: ...... Stable

HAZARDOUS DECOMP .:.... Will not occur

**INCOMPATIBILITY: .....** Oxidizers or Oxidizing Materials.

**HAZARDOUS REACTIONS:** Not expected to be Explosive, Self-Reactive, Self-Heating, or an

Organic Peroxide under US GHS Definition(s).

### 11 – TOXICOLOGICAL INFORMATION

This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydrotreating. None of the oils requires a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B). These oils have not been classified by the American Conference of Governmental Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).

THRESHOLD LIMIT VALUE:.. 100 ppm OSHA PEL:......50 ppm

**LISTED CARCINOGEN:......** No data available for the mutagenic, teratogenic, or reproductive effects

of the property. No data to designate product to cause specific target organ toxicity through repeated exposure. Health studies have shown that many petroleum hydrocarbons pose potential human health risks, which may vary, from person to person. As a precaution, exposure to

liquids, vapors, mists or fumes should be minimized.

MEDICAL CONDITION AGGRAVATED:

Existing dermatitis.



### INFORMATION ON ACUTE TOXICOLOGICAL EFFECTS

ORAL	
	. Small amounts of this product aspirated into the respiratory system
	cause mild to severe pulmonary injury, possibly progressing to death.
DERMAL	Encount on molecular and contact manifests and consider democials I am
	. Frequent or prolonged contact may irritate and cause dermatitis. Low aggravate an existing dermatitis condition.
INHALATION	
	High vapor/aerosol concentrations (attainable at elevated temperatures
	o the eyes and the respiratory tract, and may cause headaches, dizziness,
	busness, and other central nervous system effects, including death effects,
including death.	
REPEATED DOSE TOXICITY	N. 1
of the property. No data to designa	No data available for the mutagenic, teratogenic, or reproductive effects te product to cause specific target organ toxicity through repeated
exposure.	TON.
SKIN CORROSION / IRRITAT	
	Repeated and prolonged exposure to concentrated material may cause
dermatitis. SERIOUS EYE DAMAGE / IRR	OTTATION
	Practically non-irritating. Slightly irritating but does not injure eye
tissue.	• 1 factically non-inflating. Stignery inflating but does not injure eye
RESPIRATORY OR SKIN SEN	SITIZATION
	Not expected to be sensitizing based on tests of this product,
components, or similar products.	That expected to be sensitizing based on tests of this product,
MUTAGENCITY	
IN VITRO	
Product:	No Data Available
IN VIVO	
Product:	No Data Available
Specified Substance(s)	Information as provided by manufacturer
Toluene	Not Anticipated To Be A Human Carcinogen
CARCINOCENICIEN	
CARCINOGENICITY	Deced on available date the electification oritoric are not mat
REPODUCTIVE TOXICITY	Based on available data, the classification criteria are not met.
	No data available for the mutagenic, teratogenic, or reproductive effects
of the property.	• 130 data available for the indiagenic, teratogenic, or reproductive effects
	OXICITY – SINGLE EXPOSURE
	olvent vapors may be irritating to skin and eyes. <b>INHALATION:</b> High

**Product: GENERAL:** Solvent vapors may be irritating to skin and eyes. **INHALATION:** High concentrations of vapor may cause irritation of the respiratory tract, experienced as nasal discomfort and discharge, possibly with chest pain and coughing. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. **EYES:** May cause mild to severe rritation experienced as discomfort or pain, excess blinking and tear production, possibly with marked redness and swelling of the conjunctiva. **SKIN:** Brief contact may cause slight irritation with itching and local redness. Prolonged contact may cause more severe irritation, with discomfort or pain. **SWALLOWING:** May cause headache, dizziness, nausea, vomiting, diarrhea, coma, and death.



MOBILITY IN SOIL

Product: ...... Negligible

### **Safety Data Sheet** (SPEC SOL 1306)

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE **Product:** The effects of long-term, low-level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the avoidance of all effects from repetitive acute exposure. This product may aggravate existing eye, skin, and respiratory conditions. ASPIRATION HAZARD **Product:** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause chemical pneumonia. OTHER ADVERSE EFFECTS **Product:** There is no information available at this time for this product. Studies have shown that bacteria and fungi have the ability to degrade ingredients in this product thereby decreasing their toxicity to fish. However, a spill may produce significant toxicity to aquatic organisms and ecosystems. 12 - ECOLOGICAL INFORMATION ACUTE TOXICITY **FISH** is possible if continuous exposure is maintained. AQUATIC INVERTEBRATES **Product:** Product is ecotoxic. Long term adverse effects to aquatic invertebrates is possible if continuous exposure is maintained. CHRONIC TOXICITY **FISH Product:** There is no information available at this time for this product. However, a spill may produce significant toxicity to aquatic organisms and ecosystems. AQUATIC INVERTEBRATES **Product:** There is no information available at this time for this product. However, a spill may produce significant toxicity to aquatic organisms and ecosystems. TOXICITY TO AQUATIC PLANTS **Product:** Product is ecotoxic. Long term adverse effects to aquatic plants is possible if continuous exposure is maintained. PERSISTENCE AND DEGRADABILITY BIODEGRADATION **Product:** Readily biodegradable meeting the 10-day window criterion. Oxidizes rapidly by photochemical reactions in air. BIOLOGICAL OXYGEN DEMAND Product:..... CHEMICAL OXYGEN DEMAND Product: ...... No data available BOD / COD RATIO **Product:** ...... No data available **BIOACCUMULATIVE POTENTIAL Product:** Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.



### RESULTS OF PBT AND mPvB ASSESSMENT

#### OTHER ADVERSE EFFECTS

### 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: ...... Treatment, storage, transportation and disposal must be in accordance

with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in

accordance with federal, state and local requirements.

RCRA STATUS: ...... If discarded in its purchased form, this product is considered a RCRA

hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product should

be classified as a hazardous waste. (40CFR261.20-24).

#### 14 - TRANSPORTATION INFORMATION

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.



**UN/NA NUMBER: .....** 1268

PROPER SHIPPING NAME: ..... Petroleum Distillates, n.o.s., Contains (Heavy Petroleum Naphtha)

HAZARD CLASS:...... 3
PACKAGING GROUP:......III

**LETTER:** F (Highly flammable)

ENVIRONMENTAL HAZARD: Because of modern treatment methods or method of use of this product,

only an insignificant amount of the ingredients reaches the environment. That amount is at such levels as to typically not cause any adverse

effects.

REPORTABLE QUANTITY: ..... None



### **15 - REGULATIONS**

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System. This SDS complies with 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD). **IMPORTANT:** Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

### EPA SRA Title III Chemical Listings:

TSCA STATUS:	This product is listed on the TSCA inventory. If this product is a blend,
	all ingredients in the product are listed on the TSCA Inventory List.
	Any impurities present in this product are exempt from listing.
<b>SECTION 302:</b>	None
<b>SECTION 304:</b>	None
<b>SECTION 312:</b>	Yes
<b>SARA SECTION 313:</b>	The following components are subject to reporting levels established by
	SARA title III, Section 313: TOLUENE CAS# 108.90-7.
ACUTE:	Yes
CHRONIC:	Yes
FIRE:	Yes
PRESSURE:	No
REACTIVE:	No
CLEAN WATER ACT:	None

### IMDG - International Marine Dangerous Goods Code

UN1268, Petroleum Distillates, N.O.S. Contains (Heavy Petroleum Naphtha), 3, PG III. EMS-No: F-E S-E. Marine pollutant: No.

### **IATA**

UN1268, Petroleum Distillates, N.O.S. Contains (Heavy Petroleum Naphtha), 3, PG III.

**DEA Chemical Trafficking Act:..** No



### **16 - OTHER INFORMATION**

HMIS*		
HEALTH	1	
FLAMMABILITY	2	
REACTIVITY	0	
PERSONAL PROTECTIO	N H	

\*HMIS®HAZARD INDEX: 0=Minimal Hazard, 1=Slight Hazard, 2=Moderate Hazard, 3=Serious Hazard, 4=Severe Hazard. HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this SDS and product label must be considered.

ND = No Data, NA = Not Applicable/Not Available,  $\leq = Less than or equal to$ ,  $\geq = Greater than or equal to$ 

**REVISION STATEMENT:** Changes have been made throughout this Safety Data Sheet (SDS). Please read the entire document. Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and The Globally Harmonized System of Classification and Labeling of Chemicals (GHS) by the Company Health and Risk Assessment Unit.

#### **DISCLAIMER:**

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, the Company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving this Safety Data Sheet (SDS) will make their own determination as to its suitability for their intended purposes prior to use. Since the product is within the exclusive control of the user, it is the user's obligation to determine the conditions of safe use of this product. Such conditions should comply with all Federal and State Regulations concerning the Product. It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. REPRESENTATIONS OR WARRANTIES, **EITHER EXPRESS** OR IMPLIED, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

\*\*\*This is the last page of this SDS\*\*\*