



Safety Data Sheet (TT-N-95 SOLVENT)

1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:TT-N-95 SOLVENT
CHEMICAL NAME/
CLASS/SYNONYMS:Petroleum Distillates (Naphtha Solvent), Suitable for all Type 1
and Type 2 uses.
PRODUCT NUMBER:TT-N-95 SOLVENT
UN/NA NUMBER:1268
CHEMICAL FAMILY:Petroleum Solvent
CAS NUMBER:64742-49-0
FORMULA:A complex stream of predominately C9 to C12 hydrocarbons;
exact composition will vary.

COMPANY:JMN Specialties, Inc.
1100 Victory Drive – Westwego, Louisiana USA 70094
Phone (504) 341-3749, Fax (504) 341-5868
www.jmnspecialties.com

EMERGENCY PHONE:CALL CHEMTEL: Toll Free US & Canada: (800) 255-3924, Outside
USA +01-813-248-0585.

DATE PREPARED:January 18, 2021

2 – HAZARDS IDENTIFICATION

GHS HAZARD CLASSIFICATION:

Physical Hazards

Flammable Liquids:Category 2 - Highly flammable liquid and vapor
Corrosive Liquids:No Hazard Statement established for this Product

Health Hazards

Acute Toxicity (Oral):Category 4 - Harmful if swallowed, in contact with skin, inhaled
Skin Corrosion/Irritation:Category 2 - Causes skin irritation
Eye Damage/Irritation:Category 2A - Causes eye irritation
Aspiration Hazard:Category 1 - May be fatal if swallowed and enters airways
Carcinogen:Category 1B - Presumed to have carcinogenic potential for
humans

See Section 11 for additional Toxicological information

EMERGENCY OVERVIEW:

Pictograms:





Safety Data Sheet (TT-N-95 SOLVENT)

Signal Word (GHS-US):**DANGER!**

Hazard Statements:

Physical Hazards (GHS-US):

H225 Highly flammable liquid and vapor.

Health Hazards (GHS-US):

H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs (Central nervous system, Peripheral nervous system) through prolonged or repeated exposure.

Environmental Hazards (GHS-US):

H413: May cause long lasting harmful effects to aquatic life

Precautionary Statements (GHS-US):

P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe dust/fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. P281 Use personal protective equipment as required.

Response Statements (GHS-US):

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P308 + P313 IF exposed or concerned: Get medical advice/attention. P331 Do NOT induce vomiting. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P501: Dispose of contents/container: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations, and product characteristics at time of disposal.

TOTAL VOC's:.....6.13 pounds per gallon

3 – COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	PERCENT*	CAS NUMBER
Hydrotreated Light Naphtha	90 - 100	64742-49-0

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.



Safety Data Sheet (TT-N-95 SOLVENT)

4 – FIRST-AID MEASURES

- BREATHING (INHALATION):**..... Remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial resuscitation. Keep person warm and at rest. Treat symptomatically and supportively. Seek medical attention immediately. Qualified medical personnel should consider administering oxygen.
- SWALLOWING (INGESTION):**..... Give large amounts of fresh water or milk immediately. Do not give anything by mouth if person is unconscious or otherwise unable to swallow. If vomiting occurs, keep head below hips to prevent aspiration. Treat symptomatically and supportively. Seek medical attention immediately.
- EYES:** Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
- SKIN (DERMAL):** Remove contaminated clothing and wash affected skin with soap and water. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.
- NOTE TO PHYSICIAN:** All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Material, if aspirated into the lungs, may cause chemical pneumonitis. Skin contact may aggravate an existing dermatitis. Treat appropriately.

5 – FIRE-FIGHTING MEASURES

- GENERAL FIRE HAZARDS:** Flammable liquid and vapor
- AUTOIGNITION TEMP:**..... 608°F (320°C)
- EXTINGUISHING MEDIA:**..... Determined by surrounding material. In case of fire, use water fog, dry chemical, CO₂, or "alcohol" foam. Firefighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.
- SPECIAL FIRE FIGHTING PROCEDURES:**..... Spilled product on ground may be slippery.
- UNUSUAL FIRE AND EXPLOSION HAZARDS:**..... Containers may explode from internal pressure if confined to fire. Cool with water spray. Vapor accumulation could flash or explode if in contact with an open flame.



Safety Data Sheet (TT-N-95 SOLVENT)

6 – ACCIDENTAL RELEASE MEASURES

- SPILL PROCEDURES:**Wear appropriate personal protective equipment before approaching spill site. For small spills, dilute with water to sewer if allowed by local and state regulations. If unable to wash product with water, absorb with inert material (sand or other approved material) and dispose of in accordance with applicable regulations.
- WASTE DISPOSAL:**Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.
- RCRA STATUS:**If discarded in its purchased form, this product is considered a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product should be classified as a hazardous waste. (40CFR261.20-24).

7 – HANDLING and STORAGE

- STORAGE:** Keep in a tightly closed container, stored in a cool, dry, ventilated area below 44°C (110°F). Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Drum must not be washed out or used for other purposes.
- HANDLING:**Avoid contact with eyes, skin and clothing. Do not inhale vapors and fumes. Wash thoroughly after handling. Use only with adequate ventilation. Do not take internally. For industrial use only.



Safety Data Sheet (TT-N-95 SOLVENT)

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS INGREDIENT
Hydrotreated Light Naphtha

PEL
400 ppm

TLV-TWA
400 ppm



EXPOSURE CONTROLS:..... Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

RESPIRATORY PROTECTION:..... If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information. Self-Contained Breathing Apparatus may be required for use in confined or enclosed spaces.

PROTECTIVE CLOTHING:..... **Eye/face protection:** Wear chemical goggles; face shield (if splashing is possible). **Skin protection:** Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron or chemical suit and chemical resistant boots are recommended.

ADDITIONAL MEASURES:..... Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.



Safety Data Sheet (TT-N-95 SOLVENT)

9 – PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT:..... 205 - 241°F (96 - 116°C)
FREEZING POINT:..... - 99°F (- 73°C)
FLASHPOINT:50 - 60°F (10 – 15.6°C)
UPPER FLAME LIMIT (%):.....8.0 % (V)**LOWER FLAME LIMIT (%):** 0.8% (V)
VAPOR PRESSURE:30.75 mm/hg at 20.0°C
VAPOR DENSITY (AIR=1):.....3.3 (Air = 1)
SPECIFIC GRAVITY:0.75
pH:NA
SOLUBILITY IN WATER:.....Negligible
VOLATILITY
INCLUDING WATER:6.13 pounds per gallon
MOLECULAR WEIGHT:.....No data available (G/MOLE)
EVAPORATION RATE:No Data
PHYSICAL STATE:.....Liquid
COLOR:Clear
ODOR:Petroleum odor (Slight)

10 – STABILITY and REACTIVITY

STABILITY:Stable
HAZARDOUS DECOMP.:Will not occur
INCOMPATIBILITY:Oxidizers or Oxidizing Materials.
HAZARDOUS REACTIONS:..... Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).

11 – TOXICOLOGICAL INFORMATION

THRESHOLD LIMIT VALUE:.....400 ppm
OSHA PEL:.....100 ppm
LISTED CARCINOGEN:.....Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. This product contains ingredients listed as carcinogenic or a potential carcinogen by the National Toxicology Program, by the I.A.R.C. monographs, or by OSHA. No toxicity to reproduction. No evidence of adverse effects on sexual function and fertility, and on development, based on animal experiments.
MEDICAL CONDITION
AGGRAVATED:..... Existing dermatitis.

INFORMATION ON ACUTE TOXICOLOGICAL EFFECTS



Safety Data Sheet (TT-N-95 SOLVENT)

ORAL

Product:Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

DERMAL

Product:This product is a skin irritant. It may be absorbed through the skin. It may cause irritation, dermatitis, drying of skin, and numbness in fingers and arms. May increase severity of symptoms listed under inhalation.

INHALATION

Product:High vapor/aerosol concentrations are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anaesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

REPEATED DOSE TOXICITY

Product:No data available for the mutagenic, teratogenic, or reproductive effects of the property. No data to designate product to cause specific target organ toxicity through repeated exposure.

SKIN CORROSION / IRRITATION

Product:Repeated and prolonged exposure to concentrated material may cause dermatitis.

SERIOUS EYE DAMAGE / IRRITATION

Product:This material is an eye irritant. It may cause irritation, redness, stinging, tearing, excessive swelling of the conjunctiva; and or excessive blinking.

RESPIRATORY OR SKIN SENSITIZATION

Product:Not expected to be sensitizing based on tests of this product, components, or similar products.

MUTAGENICITY

IN VITRO

Product:No Data Available

IN VIVO

Product:No Data Available

Specified Substance(s)

Information as provided by manufacturer

Hydrotreated light naphtha

No Data Available

CARCINOGENICITY

Product:

REPRODUCTIVE TOXICITY

Product:No data available for the mutagenic, teratogenic, or reproductive effects of the property.

SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE



Safety Data Sheet (TT-N-95 SOLVENT)

Product:..... **GENERAL:** Solvent vapors may be irritating to skin and eyes.
INHALATION: High concentrations of vapor may cause irritation of the respiratory tract, experienced as nasal discomfort and discharge, possibly with chest pain and coughing. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. **EYES:** May cause mild to severe irritation experienced as discomfort or pain, excess blinking and tear production, possibly with marked redness and swelling of the conjunctiva. **SKIN:** Brief contact may cause slight irritation with itching and local redness. Prolonged contact may cause more severe irritation, with discomfort or pain. **SWALLOWING:** May cause headache, dizziness, nausea, vomiting, diarrhea, coma, and death.

SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE

Product:The effects of long-term, low-level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the avoidance of all effects from repetitive acute exposure. This product may aggravate existing eye, skin, and respiratory conditions.

ASPIRATION HAZARD

Product:Droplets of the product aspirated into the lungs through ingestion or vomiting may cause chemical pneumonia.

OTHER ADVERSE EFFECTS

Product:Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances. Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

12 – ECOLOGICAL INFORMATION

ACUTE TOXICITY

FISH

Product:LC50 (Oncorhynchus mykiss (rainbow trout)): 8.2 mg/l Exposure time: 96 h Test Type: semi-static test.

AQUATIC INVERTEBRATES

Product:EC50 (Daphnia magna (Water flea)): 4.5 mg/l Exposure time: 48 h Test Type: Immobilization.

CHRONIC TOXICITY

FISH

Product: Toxic to fish. Estimated based on individual component values.

AQUATIC INVERTEBRATES

Product:Toxic to aquatic life with long lasting effects.

TOXICITY TO AQUATIC PLANTS

Product:EC50 (Pseudokirchneriella subcapitata (green algae)): 3.7mg/l Exposure time: 96 h Test Type: static test.

PERSISTENCE AND DEGRADABILITY



Safety Data Sheet (TT-N-95 SOLVENT)

BIODEGRADATION

Product:Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

BIOLOGICAL OXYGEN DEMAND

Product:No data available

CHEMICAL OXYGEN DEMAND

Product:No data available

BOD / COD RATIO

Product:No data available

BIOACCUMULATIVE POTENTIAL

Product:Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

MOBILITY IN SOIL

Product:Negligible

RESULTS OF PBT AND mPvB ASSESSMENT

Product:Not fulfilling PBT (persistent/bioaccumulative/toxic) criteria.
Not fulfilling vPvB (very persistent, very bioaccumulative) criteria.

OTHER ADVERSE EFFECTS

Product:No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential or global warming potential) are expected from this product.

13 –DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:.....Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

RCRA STATUS:.....If discarded in its purchased form, this product is considered a RCRA hazardous waste. It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product should be classified as a hazardous waste. (40CFR261.20-24).



Safety Data Sheet (TT-N-95 SOLVENT)

14 – TRANSPORTATION INFORMATION

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.



UN/NA NUMBER:.....1268
PROPER SHIPPING NAME:..... Petroleum Distillates, n.o.s., Contains (Hydrotreated light naphtha)
HAZARD CLASS:.....3
PACKAGING GROUP :.....II
LETTER:.....F (Highly flammable)
ENVIRONMENTAL HAZARD:Because of modern treatment methods or method of use of this product, only an insignificant amount of the ingredients reaches the environment. That amount is at such levels as to typically not cause any adverse effects.
REPORTABLE QUANTITY:.....Mixed Xylenes, cas# 1330-20-7, RQ 100#. Calculated RQ exceeds reasonably attainable upper limit for this product.

15 - REGULATIONS

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System. This SDS complies with 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD). **IMPORTANT:** Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

EPA SRA Title III Chemical Listings:

TSCA STATUS:This product is listed on the TSCA inventory. If this product is a blend, all ingredients in the product are listed on the TSCA Inventory List. Any impurities present in this product are exempt from listing.
SECTION 302:.....No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SECTION 304:.....This material does not contain any components with a section 304 EHS RQ.
SECTION 312:.....Yes
SARA SECTION 313:.....This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
ACUTE:Yes
CHRONIC:Yes



Safety Data Sheet (TT-N-95 SOLVENT)

FIRE:Yes
PRESSURE: No
REACTIVE:No
CLEAN WATER ACT:.....None

IMDG – International Marine Dangerous Goods Code

UN1268, Petroleum Distillates, N.O.S. Contains (Hydrotreated light naphtha), 3, PG II. EMS-No: F-E S-E. Marine pollutant: No.

IATA

UN1268, Petroleum Distillates, N.O.S. Contains (Hydrotreated light naphtha), 3, PG II.

DEA Chemical Trafficking Act: ..No

Homeland Security Regulated ..This product does not contain any reportable DHS chemicals.

California Proposition 65.....This product contains the following Proposition 65 chemicals:

Component.....Distillates, petroleum light distillate hydrotreat process, low-boil AND/OR Naphtha (pet), hydrotreated light AND/OR Solvent naphtha petroleum light aliphatic, cas# 68410-97-9 / 64742-49-0 / 64742-89-8.

Cal Prop 65..... Known to the State of California to be a carcinogen.

Cal Prop 65 NSRL.....Chronic Reference Exposure Levels

Category..... Known to the State of California to be a carcinogen.

US State Right to Know (RTK)

Component.....Distillates, petroleum light distillate hydrotreat process, low-boil AND/OR Naphtha (pet), hydrotreated light AND/OR Solvent naphtha petroleum light aliphatic, cas# 68410-97-9 / 64742-49-0 / 64742-89-8.

MassachusettsYes **

New JerseyYes **

PennsylvaniaYes **

IllinoisYes **

Rhode Island.....Yes **

****RTK Chemical(s)** ** Distillates, petroleum light distillate hydrotreat process, low-boil AND/OR Naphtha (pet), hydrotreated light AND/OR Solvent naphtha petroleum light aliphatic, cas# 68410-97-9 / 64742-49-0 / 64742-89-8, 90 - 100 %. Octane, cas# 111-65-9, 1 - 5 %. Mixed Xylenes, cas# 1330-20-7, 0.1 - 1 %. Toluene, cas# 108-88-3, 0 - 0.1 %. Benzene, cas# 71-43-2, 0 - 0.1 %. Ethylbenzene, cas# 100-41-4, 0 - 0.1 %. m-Xylene, cas# 108-38-3, 0 - 0.1 %. Naphthalene, cas# 91-20-3, 0.1 - 1 %. Contains chemicals known to the State of California to cause birth defects or other reproductive harm: Toluene, cas# 108-88-3, Benzene, cas# 71-43-2.



Safety Data Sheet (TT-N-95 SOLVENT)

Canada NPRIDistillates, petroleum light distillate hydrotreat process, low-boil AND/OR Naphtha (pet), hydrotreated light AND/OR Solvent naphtha petroleum light aliphatic, cas# 68410-97-9 / 64742-49-0 / 64742-89-8.

DSL (Canadian Domestic Substances List) and CEPA (Canadian Environmental Protection Act): All ingredients in this product are listed on the DSL. Any impurities present in this product are exempt from listing.

AICS / NICNAS (Australian Inventory of Chemical Substances and National Industrial Chemicals Notification and Assessment Scheme): All ingredients in this product are listed on AICS or otherwise complies with NICNAS.

MITI (Japanese Handbook of Existing and New Chemical Substances): All ingredients in this product are listed in the Handbook or has been approved in Japan by new substance notification.

ECL (Korean Toxic Substances Control Act): All ingredients in this product are listed on the Korean inventory or otherwise complies with the Korean Toxic Substances Control Act.KE-04134

Philippines Inventory (PICCS): All ingredients in this product are listed on the Philippine Inventory or otherwise complies with PICCS.

Inventory of Existing Chemical Substances in China: All ingredients in this product are listed on the Inventory of Existing Chemical Substances in China (IECSC).



Safety Data Sheet (TT-N-95 SOLVENT)

16 – OTHER INFORMATION

HMIS*

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	H

**HMIS®HAZARD INDEX: 0=Minimal Hazard, 1=Slight Hazard, 2=Moderate Hazard, 3=Serious Hazard, 4=Severe Hazard.*

HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this SDS and product label must be considered.

ND = No Data, NA = Not Applicable/Not Available, ≤ = Less than or equal to, ≥ = Greater than or equal to

REVISION STATEMENT: Changes have been made throughout this Safety Data Sheet (SDS). Please read the entire document. Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and The Globally Harmonized System of Classification and Labeling of Chemicals (GHS) by the Company Health and Risk Assessment Unit.

DISCLAIMER:

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, the Company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving this Safety Data Sheet (SDS) will make their own determination as to its suitability for their intended purposes prior to use. Since the product is within the exclusive control of the user, it is the user's obligation to determine the conditions of safe use of this product. Such conditions should comply with all Federal and State Regulations concerning the Product. It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. **NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.**

*****This is the last page of this SDS*****