

1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME:	. SANITIZING HAND GEL
CHEMICAL NAME/	
CLASS/SYNONYMS:	• This is a personal hand cleaning product that is safe for consumers and
	other users under normal use.
PRODUCT NUMBER:	. SANITIZING HAND GEL
UN/NA NUMBER:	. 1987
CHEMICAL FAMILY:	. Alcohol
CAS NUMBER:	• Not applicable for mixtures.
FORMULA:	Mixture
COMPANY:	. JMN Specialties, Inc.
COMPANY:	
COMPANY:	1100 Victory Drive – Westwego, Louisiana USA 70094
COMPANY:	1100 Victory Drive – Westwego, Louisiana USA 70094 Phone (504) 341-3749, Fax (504) 341-5868
	1100 Victory Drive – Westwego, Louisiana USA 70094
	1100 Victory Drive – Westwego, Louisiana USA 70094 Phone (504) 341-3749, Fax (504) 341-5868 www.jmnspecialties.com
	 1100 Victory Drive – Westwego, Louisiana USA 70094 Phone (504) 341-3749, Fax (504) 341-5868 www.jmnspecialties.com CALL CHEMTEL: Toll Free US & Canada: (800) 255-3924, Outside USA +01-813-248-0585.

2 – HAZARDS IDENTIFICATION

GHS HAZARD CLASSIFICATION:

WARNING LABEL ITEMS INCLUDING PRECAUTIONARY STATEMENTS:

Pictograms:



SIGNAL WORD: DANGER!

GHS HAZARD AND PRECAUTIONARY STATEMENTS:

H303 H313 H333: May be harmful if swallowed, in contact with skin or if inhaled H305: May be harmful if swallowed and enters airways

P101+102+103: If medical advice is needed, have product container or label at hand. Keep out of the reach of children. Read label before use.

P202+270+280+281: Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.



P501: Dispose of contents/container: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

TOTAL VOC's: 4.90 pounds per gallon

3 – COMPOSITION / INFORMATION ON INGREDIENTS		
HAZARDOUS INGREDIENT	PERCENT*	CAS NUMBER
FDA SDA 40B Ethanol	60 - 70	64-17-5
Isopropyl Alcohol	0 - 5	67-63-0

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4 – FIRST-AID MEASURES

	 Remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial resuscitation. Keep person warm and at rest. Treat symptomatically and supportively. Seek medical attention immediately. Qualified medical personnel should consider administering oxygen. Give large amounts of fresh water or milk immediately. Do not give anything by mouth if person is unconscious or otherwise unable to swallow. If vomiting occurs, keep head below hips to prevent aspiration. Treat symptomatically and supportively. Seek medical attention immediately.
EYES:	. Flush eye with copious quantities of water. If persistent irritation
	 occurs, obtain medical attention. Remove contaminated clothing and wash affected skin with soap and water. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Material, if aspirated into the lungs, may cause chemical pneumonitis. Skin contact may aggravate an existing dermatitis. Treat appropriately.

5 – FIRE-FIGHTING MEASURES

GENERAL FIRE HAZARDS:	. Flammable liquid and vapor
AUTOIGNITION TEMP:	. 689°F (365°C) (Ethanol)
EXTINGUISHING MEDIA:	Determined by surrounding material. In case of fire, use water fog, dry
	chemical, CO ₂ , or "alcohol" foam. Firefighting should be attempted



only by those who are adequately trained and equipped with proper protective equipment.

	protective equipment.
SPECIAL FIRE FIGHTING	
PROCEDURES:	Spilled product on ground may be slippery.
UNUSUAL FIRE AND	
EXPLOSION HAZARDS:	Containers may explode from internal pressure if confined to fire. Cool
	with water spray. Vapor accumulation could flash or explode if in
	contact with an open flame.

6 – ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:	. Wear appropriate personal protective equipment before approaching
	spill site. For small spills, dilute with water to sewer if allowed by local and state regulations. If unable to wash product with water, absorb with inert material (sand or other approved material) and dispose of in accordance with applicable regulations.
WASTE DISPOSAL:	Treatment, storage, transportation and disposal must be in accordance
	with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in
	accordance with federal, state and local requirements.
RCRA STATUS:	If discarded in its purchased form, this product is considered a RCRA hazardous waste. It is the responsibility of the product user to
	determine at the time of disposal, whether a material containing the product should be classified as a hazardous waste. (40CFR261.20-24).

7 – HANDLING and STORAGE

STORAGE:	Keep in a tightly closed container, stored in a cool, dry, ventilated area below 44°C (110°F). Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Drum must not be
HANDLING:	washed out or used for other purposes. Avoid contact with eyes, skin and clothing. Do not inhale vapors and fumes. Wash thoroughly after handling. Use only with adequate ventilation. Do not take internally. For industrial use only.

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS INGREDIENT FDA SDA 40B Ethanol Isopropyl Alcohol **PEL** 1000 ppm 400 ppm **TLV-TWA** 1000 ppm 400 ppm





EXPOSURE CONTROLS:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

RESPIRATORY PROTECTION: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information. Self-Contained Breathing Apparatus may be required for use in confined or enclosed spaces.
 PROTECTIVE CLOTHING:

OTHING: Eye/face protection: Wear chemical goggles; face shield (if splasning is possible). Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron or chemical suit and chemical resistant boots are recommended.

ADDITIONAL MEASURES: Handle in accordance with good industrial hygiene and safety practice.

9 – PHYSICAL / CHEMICAL PROPERITES

BOILING POINT:	
FREEZING POINT:	< 0°F (< -17°C)
FLASHPOINT:	64.9°F (18.3°C)
UPPER FLAME LIMIT (%):	
LOWER FLAME LIMIT (%):	2.0%
VAPOR PRESSURE:	Weighted average: 3.77 kPa @ 20°C
VAPOR DENSITY (AIR=1):	Weighted average: 1.67 (Air = 1)
SPECIFIC GRAVITY:	0.84
pH:	NA
SOLUBILITY IN WATER:	Miscible
VOLATILITY	
INCLUDING WATER:	6.20 pounds per gallon
MOLECULAR WEIGHT:	No data available (G/MOLE)
EVAPORATION RATE:	ND
PHYSICAL STATE:	Liquid
COLOR:	Clear
ODOR:	Sharp, Alcohol



10 – STABILITY and REACTIVITY

 STABILITY:
 Stable

 HAZARDOUS DECOMP.:
 Will not occur

 INCOMPATIBILITY:
 Oxidizers or Oxidizing Materials.

 HAZARDOUS REACTIONS:
 Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).

11 – TOXICOLOGICAL INFORMATION

Cancer: Research shows that the Solvents used in the mixture are unlikely to cause cancer. **Reproductive Effects:** There are no indications that the Solvents used in the mixture causes damage to reproductive organs. Solvents may affect the development of unborn babies. **Organ Systems:** Damage to the brain, liver, bone marrow and kidneys can occur with repeated or excessive inhalation of any solvent vapors.

THRESHOLD LIMIT VALUE: . No occupational exposure limits have been established at this time.	
OSHA PEL:	None Established for this Product
LISTED CARCINOGEN:	This product IS NOT listed in the National Toxicology Program (NTP)
	Report on Carcinogens (latest edition) or has been found to be a
	potential carcinogen in the International Agency for Research on
	Cancer (IARC) Monographs (latest editions) or found to be a potential
	carcinogen by OSHA.
MEDICAL CONDITION	
AGGRAVATED:	Existing dermatitis.

INFORMATION ON ACUTE TOXICOLOGICAL EFFECTS

ORAL

Product: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion of this product may result in central nervous system depression including headache, weakness, dizziness, loss of coordination and judgement and coma. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury, possibly death. Ingestion of this product may cause diarrhoea & stomach discomfort – not a route of industrial exposure. **DERMAL**

INHALATION

Product: Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. May cause narcotic effects in high concentration. Causes upper respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

REPEATED DOSE TOXICITY

Product:......Product is a colorless, flammable liquid with typical alcohol odor. Chronic exposure is harmful by inhalation, when in contact with the skin and if it is swallowed. Liquid and



vapor may be irritating to the eyes, skin and respiratory system. Product may cause central nervous system (CNS) depression characterized by nausea, dizziness, headache, lack of coordination, loss of consciousness and coma.

SKIN CORROSION / IRRITATION

dermatitis.

SERIOUS EYE DAMAGE / IRRITATION

Product: Produces irritation, characterized by a burning sensation, redness, tearing, inflammation, and possible corneal injury. May cause transient corneal injury. **RESPIRATORY OR SKIN SENSITIZATION**

components, or similar products.

MUTAGENCITY

IN VITRO

Product: No Data Available **IN VIVO**

Product: No Data Available

Specified Substance(s)

Information as provided by manufacturer

Isopropyl Alcohol (Isopropanol)

CARCINOGENICITY

REPODUCTIVE TOXICITY

classified as hazardous.

No Data Available

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

Product: **GENERAL:** Solvent vapors may be irritating to skin and eyes. **INHALATION:** High concentrations of vapor may cause irritation of the respiratory tract, experienced as nasal discomfort and discharge, possibly with chest pain and coughing. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. EYES: May cause mild to severe rritation experienced as discomfort or pain, excess blinking and tear production, possibly with marked redness and swelling of the conjunctiva. SKIN: Brief contact may cause slight irritation with itching and local redness. Prolonged contact may cause more severe irritation, with discomfort or pain. SWALLOWING: May cause headache, dizziness, nausea, vomiting, diarrhea, coma, and death.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE

been determined. Safe handling of this material on a long-term basis should emphasize the avoidance of all effects from repetitive acute exposure. This product may aggravate existing eye, skin, and respiratory conditions.

ASPIRATION HAZARD

vomiting may cause chemical pneumonia.

OTHER ADVERSE EFFECTS



12 – ECOLOGICAL INFORMATION

ACUTE TOXICITY

FISH

Product:......LC₅₀ (mg/L) 96 hours: Pimephales promelas: 9,640 mg/L AQUATIC INVERTEBRATES

Product: EC₅₀ 24 hours: Water flea - 5,102 mg/L

CHRONIC TOXICITY

FISH

Product:......NOEC/NOEL > 100 mg/l. (based on similar products / components) AQUATIC INVERTEBRATES

Product:......NOEC/NOEL > 100 mg/l. (based on similar products / components) **TOXICITY TO AQUATIC PLANTS**

Product: EC₅₀ 72 hours: Desmodesmus subspicatus > 2,000 mg/L

PERSISTENCE AND DEGRADABILITY

BIODEGRADATION

Product:..... Relatively Biodegradable.

BIOLOGICAL OXYGEN DEMAND

Product:......Biodegradation: 58% theoretical BOD, 5 days at 20° C - Relatively biogradeable.

CHEMICAL OXYGEN DEMAND

BOD / COD RATIO

Product: No data available

BIOACCUMULATIVE POTENTIAL

MOBILITY IN SOIL

OTHER ADVERSE EFFECTS

Product: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal



disposal regulations. Dispose of container and unused contents in
accordance with federal, state and local requirements.RCRA STATUS:If discarded in its purchased form, this product is considered a RCRA
hazardous waste. It is the responsibility of the product user to
determine at the time of disposal, whether a material containing the
product should be classified as a hazardous waste. (40CFR261.20-24).

14 – TRANSPORTATION INFORMATION

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.



REPORTABLE QUANTITY: None

15 - REGULATIONS

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System. This SDS complies with 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD). **IMPORTANT:** Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

EPA SRA Title III Chemical Listings:

TSCA STATUS:	• This product is listed on the TSCA inventory. If this product is a blend, all ingredients in the product are listed on the TSCA Inventory List. Any impurities present in this product are exempt from listing.
SECTION 302:	. None
SECTION 304:	. None
SECTION 312:	. None
SARA SECTION 313:	Isopropyl alcohol: CAS # 67-63-0; 5000 Lbs. (2267.962 Kilograms).
	Threshold Planning Quantity (TPQ)
ACUTE:	. Yes
CHRONIC:	. No
FIRE:	. Yes
PRESSURE:	. No
REACTIVE:	. No
CLEAN WATER ACT:	. None
IMDG – International Marine D	angerous Goods Code
UN1987, Alcohols, n.o.s. (Ethanol	, Isopropyl Alcohol), 3, F, PGIII. Marine Pollutant: No Static
Accumulator: Yes. EMS-No: F-E,	S-D
IATA	



UN1987, Alcohols, n.o.s. (Ethanol, Isopropyl Alcohol), 3, F, PGIII. **DEA Chemical Trafficking Act:..** No

16 – OTHER INFORMATION

HMIS*		
HEALTH		1
FLAMMABILITY		3
REACTIVITY		0
PERSONAL PROTECTION		Х

*HMIS®HAZARD INDEX: 0=Minimal Hazard, 1=Slight Hazard, 2=Moderate Hazard, 3=Serious Hazard, 4=Severe Hazard. HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this SDS and product label must be considered.

ND = No Data, NA = Not Applicable/Not Available, \leq = Less than or equal to, \geq = Greater than or equal to

REVISION STATEMENT: Changes have been made throughout this Safety Data Sheet (SDS). Please read the entire document. Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and The Globally Harmonized System of Classification and Labeling of Chemicals (GHS) by the Company Health and Risk Assessment Unit.

DISCLAIMER:

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, the Company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving this Safety Data Sheet (SDS) will make their own determination as to its suitability for their intended purposes prior to use. Since the product is within the exclusive control of the user, it is the user's obligation to determine the conditions of safe use of this product. Such conditions should comply with all Federal and State Regulations concerning the Product. It must be recognized that the physical and chemical properties of any product may not be fully understood and that new, possibly hazardous products may arise from reactions between chemicals. The information given in this data sheet is based on our present knowledge and shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. NO REPRESENTATIONS OR WARRANTIES, EITHER **EXPRESS** OR IMPLIED, OF MERCHANTABILITY. FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH **INFORMATION REFERS.**

This is the last page of this SDS